



Aqua Chemical Supply, Inc.

183 Moore Street – Millersburg – PA – 17061
Office 717-692-7369 / 1-866-375-2782 Fax 717-692-3280

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identity ECO-CHOICE Rubber Diluent

Alternate Names ECO-CHOICE Rubber Diluent

Manufacturer/Supplier/Distributor:
Sau-Sea Swimming Pool Products, Inc.
1855 Highway 206 South
Southampton, New Jersey 08088
Emergency telephone number: For emergency assistance involving chemicals call
CHEMTREC day or night at: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Highly Flammable liquid and vapor.
Skin Irrit. Causes skin irritation.
Eye Irrit. Causes serious eye irritation.
STOT SE May cause respiratory irritation.



Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation
[Prevention]:
Keep away from heat / sparks / open flames / hot surfaces - No smoking. Keep cool.
Ground / bond container and receiving equipment.
Use explosion-proof electrical / ventilating / light / equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust / fume / gas / mist / vapors / spray. Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves / eye protection / face protection.
[Response]:
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
Specific treatment (see information on this label). If skin irritation occurs: Get medical advice / attention.
If eye irritation persists: Get medical advice / attention.
Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Take off contaminated clothing and wash before reuse.
In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.
[Storage]:
Store in a well ventilated place. Keep container tightly closed. P405 Store locked up.
[Disposal]:
Dispose of contents / container in accordance with local / national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
----------------------------------	----------	--------------------	-------

NJ TRSN 222664720-5000

CAS Number: Proprietary 100 Skin Irrit. Eye Irrit. STOT SE [1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard

Composition comments: All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Most important symptoms and effects, both acute and delayed	
Overview	May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breath fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Acute Potential Health Effects/Routes of Entry	
Inhalation:	May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.
Eyes:	Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.
Ingestion:	May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.
Skin:	May cause moderate irritation.
Acute (Immediate) Overexposure:	Can lead to central nervous system depression, producing such effects as giddiness, headache, and nausea. In extreme cases, unconsciousness and death may occur.
Chronic (Delayed) Overexposure:	Irritation to eyes, nose and throat. Prolonged and repeated liquid contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis.
Medical Conditions Aggravated by exposure:	Pre-existing eye, skin, and respiratory disorders may be aggravated by exposure to this product.
Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.	
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin.	
Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.	
Inhalation	May cause respiratory irritation.
Eyes	Causes serious eye irritation.
Skin	Causes skin irritation.

5. FIRE FIGHTING MEASURES

Extinguishing media Foam, Dry Chemical, Water Fog or CO2. Do not use a direct stream of water.

Special hazards arising from the substance or mixture Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide. Keep away from heat / sparks / open flames / hot surfaces - No smoking. Keep cool. Ground / bond container and receiving equipment. Use explosion-proof electrical / ventilating / light / equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust / fume / gas / mist / vapors / spray.

Advice for fire-fighters Wear full fire-fighting gear (full Bunker gear) and respiratory protection (SCBA). Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point.

Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Water may be used to cool containers to minimize pressure build-up. Empty containers may contain ignitable vapors.
ERG Guide No. 127

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Put on appropriate personal protective equipment (see section 8).

Environmental precautions Do not allow spills to enter drains or waterways. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Methods and material for containment and cleaning up Warning: Flammable Liquid. Keep away from heat, sparks, and open flame! Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Avoid contact with material.

Small Spills: Take up with absorbent material and place in non-leaking containers. Seal tightly for proper disposal.

Large Spills: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike, contain and keep out of water courses. If vapor cloud forms, water fog may be used to suppress. Soak up residue with absorbent material such as clay, sand, or other suitable material. Place in non-leaking container for proper disposal. Flush area to remove trace residue.

Water Disposal Method: Comply with all applicable federal, state, and local regulations doe disposal of ignitable hazard waste material used for clean-up.

7. HANDLING AND STORAGE

Precautions for safe handling

Prevent inhalation of vapor, ingestion, and contact with skin, eyes, and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapors may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store upright in sealed containers in a cool, dry, ventilated, warehouse location.

Conditions for safe storage, including any incompatibilities Handle containers carefully to prevent damage and spillage. Incompatible materials: Strong oxidizing agents and acids.

Specific end use(s) No data available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure

CAS No.	Ingredient	Source	Value
Proprietary	NJ TRSN 222664720-5000	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
Proprietary	NJ TRSN 222664720-5000	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Exposure controls

Respiratory Avoid prolonged or repeated breathing of vapors. If exposure exceeds occupational exposure limits, use a NIOSH-approved respirator to prevent overexposure. In accord with 29CFR 1910.134 use either a full-face atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

Eyes Wear splash-proof chemical safety goggles. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eyewash facilities readily available.

Skin Wear clean protective clothing and footwear to prevent skin contact. Use explosion-proof ventilation, as required, to control vapor concentrations. Rubber, polyvinyl chloride, or polyethylene gloves are recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colorless Liquid
Odor	Solvent Odor
Odor threshold	Not determined
pH	N/A
Melting point / freezing point	N.D.
Initial boiling point and boiling range	~245 degrees Fahrenheit (118 degrees C)
Flash Point	<70 F, <21 C Method Tag Closed Cup
Evaporation rate (Ether = 1)	Slower than n-Butyl Acetate
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.13%(V) Solvent Upper Explosive Limit: 7%(V) Solvent
Vapor pressure (Pa)	N.D.
Vapor Density	Heavier than Air
Specific Gravity	.86
Solubility in Water	Negligible Partition coefficient n-octanol/water (Log Kow)
Not Measured Auto-ignition temperature	Not Available
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Percent Volatile (by volume)	100 %
Reactivity in Water	Non-reactive in Water
Regulatory VOC (less water and exempt solvent):<= 340 g/l, VOC Method 310: 27%	

10. STABILITY AND REACTIVITY

Reactivity Hazardous Polymerization will not occur.
 Chemical stability Stable under normal circumstances.
 Possibility of hazardous reactions No data available.
 Conditions to avoid Excessive heat and open flame.
 Incompatible materials Strong oxidizing agents and acids.
 Hazardous decomposition products High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

Acute toxicity Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient NJ TRSN 222664720-5000 - (Proprietary)

Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation 2		Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable

Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause respiratory irritation.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. ECOLOGICAL INFORMATION

Aquatic Ecotoxicity

Ingredient 96 hr LC50 fish, mg/l 48 hr EC50 crustacea, mg/l ErC50 algae, mg/l
 NJ TRSN 222664720-5000 - (Proprietary) Not Available Not Available Not Available
 Persistence and degradability There is no data available on the preparation itself.
 Bioaccumulative potential Not Measured
 Mobility in soil No data available.
 Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals.
 Other adverse effects No data available

13. DISPOSAL CONSIDERATION

Waste treatment methods Observe all federal, state and local regulations when disposing of this substance.

14. TRANSPORT INFORMATION

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)		ICAO/IATA
UN number	UN1263	UN1263		UN1263
UN proper shipping name	UN1263, Paint Related	Material, 3, II Paint Related Material		Paint Related Material
Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3	Air Class: 3	
Packing group	II II II			
Environmental hazards	IMDG	Marine Pollutant: No;		
Special precautions for user	No further information			

15. REGULATORY INFORMATION

Regulatory Overview Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.
 WHMIS Classification B2 D2B
 US EPA Tier II Hazards Fire: Yes Sudden Release of Pressure: No
 Reactive: No Immediate (Acute): Yes Delayed (Chronic): No
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 EPCRA 302 Extremely Hazardous:
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 EPCRA 313 Toxic Chemicals:
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 Proposition 65 - Carcinogens (>0.0%):
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 Proposition 65 - Developmental Toxins (>0.0%):
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 Proposition 65 - Female Repro Toxins (>0.0%):
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 Proposition 65 - Male Repro Toxins (>0.0%):
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 New Jersey RTK Substances (>1%):
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.
 Pennsylvania RTK Substances (>1%):
 To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

16. OTHER INFORMATION

Notice

Aqua Chemical Supply, Inc. expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Aqua Chemical Supply, Inc. sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Aqua Chemical Supply, Inc. makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Aqua Chemical Supply, Inc.'s control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.